




TOUCHLESS
FINGERPRINTING

3D TERMINAL

Three-dimensional and contact-free terminal for highest security and multifunctionality at point of access.


- 3D touchless technology
- Access Control, Time and Attendance (T&A)
- In- and outdoor use
- Flush or surface mount
- Highest security level
- Superior identification performance
- No "Failure to Enroll"
- Identification or verification
- Small- and large-sized user groups
- Personalizable touchscreen
- Variable configuration and customizing
- Optional RFID, camera, liveness detection
- Stand-alone and network capability
- Hygienic for sensitive applications



reddot design award
honourable mention




3D TERMINAL



160 mm

Flush mount

Wall mount



1 = extendable
 (•)² = outside of device
 3 = extendable
 (•)⁴ = required if not sheltered

•⁵ = Requires Bluetooth module and BM Mobile
 (2)⁶ = Requires internal relay board
 (1)⁷ = Relay Type – 'Normally open only'

	3D TERMINAL	2D EYE	2D+ TERMINAL	2D TERMINAL HEAVY/DUTY	2D TERMINAL	2D STATION	2D MINI	2D MINI/HOME
Applications	Access Control	•	•	•	•	•	•	•
	Time & Attendance	•	•	•	•	in/out	in/out	
	Civil / Criminal							
Sensor	Touchless, 3D-Multiview	•						
	2D-Camera		•					
	Optical Touch, FBI-certified					•	•	
	Capacitive Touch						•	•
	Multispectral			•	•			
User Interface	7.0" Touchscreen							
	5.0" Touchscreen	•	•	•	•			
	3.5" Touchscreen					•		
	RFID	(•)	•	(•)	(•)	(•)	•	
	PIN	•	•	•	•	•		
	Loudspeaker	•	•	•	•			
	Beeper					•	•	•
Biometrics	Identifications (1:N)	•	•	•	•	•	•	•
	Verification (1:1)	•	•	•	•	•	•	•
	1:N Database Size Limit	10'000 ¹	10'000	10'000 ¹	10'000 ¹	5'000	5'000	5'000
	1:1 Database Size Limit	100'000	100'000	100'000	100'000	100'000	100'000	100'000
	FRR at FAR 1:100'000	<0.5%	<0.5%	<1.0%	<1.0%	<2.0%	<2.0%	<2.0%
	Standalone Capability	•	•	•	•	• ⁵	• ⁵	• ⁵
	Communication	LAN	•	•	•	•	•	•
	WLAN	(•)	(•)	(•)	(•)	(•) ²	(•) ²	
Interfaces	RS 232 / RS 485 (OSDP)	•	•	•	•	•	•	
	Wiegand	•	•	•	•	•	•	
	Relay Output	(2) ⁶	1	2	2	(1) ⁷	(1) ⁷	(1) ⁷
	I/O	(1/1)	2/-	2/2	2/2			
Security	Liveness Detection	(•)	(•)	(•)	(•)			
	Multi-level Data Encryption	•	•	•	•	•	•	
	Template on Card	(•)	(•)	(•)	(•)	(•)	(•)	
	Anti-tampering / Silent Alarm	(•)	(•)	(•)	(•)	(•)	(•)	
Conditions	Input Supply Voltage DC	9-30V	12V	9-30V	9-30V	9-30V	9-30V	
	Max. Power Rating	25W	36W	15W	15W	15W	10W	
	Operation Temperature in C	-20-60	0-45	-20-60	-20-60	-20-60	-20-60	
	Humidity 10-90%	•	•	•	•	•	•	
	Mounting	Wall mount ⁽³⁾	•	•	•	•	•	•
	Flush mount / Outdoor ⁽³⁾	•		•	•	•	•	
	Outdoor kit ⁽³⁾	(•) ⁴			(•) ⁴	(•) ⁴	(•) ⁴	
Certifications	CE	•	•	•	•	•	•	

Touchless Biometric Systems AG
 Rietbrunnen 2
 8808 Pfäffikon SZ
 Switzerland
 tbs@tbs-biometrics.com
 www.tbs-biometrics.com